



ENGLISH

T6442ST5V 1A UK Plugtop to Micro USB



Features:

- Fitted with Micro USB
- Small & Compact UK Plug design
- Protections: Over Voltage, Short circuit & Over Current
- Approvals: CE
- Level VI ErP/EuP efficiency compliant
- MTBF >50,000 hours
- 1 Year Warranty



ENGLISH

Characteristics	
RS Stock No	1314662
Part Number	T6442ST
Output Voltage	+5V
Output Current Max	1A
Output Current Min	0.05A
Output Power	5W
Line Regulation	+/- 3%
Ripple and Noise	200 mVp-p Maximum
Protections	Over Voltage: Output voltage shall be clamped by internal protection zener Short Circuit: Output shut down and auto restart Over Current
Output Cord	1500mm Micro USB 5PIN
Rated Input Voltage	100-240Vac
Full Input Voltage Range	90-264Vac
Rated Frequency	50-60Hz
Full Frequency Range	47-63Hz
Input Current	0.2A
Input Plug	UK 3 Pin Plugtop
Model Number	DSA-6PFG-05 FUK 050100
Dimensions	67mm X 49.55mm X 64.8mm
Weight	80g
Leakage	0.25mA max
Operating Temperature	0°C to 40°C
Storage Temperature	-20°C to 60°C
Operating Humidity	20% to 85%
Storage Humidity	5% to 95%
Safety Standard	T-License (BS EN60950-1)
EMI Standard	CE (EN55022)
MTBF	50K Hours (mean time before failure)